

Specifications

Model		SCC-A2313
Imaging Device		1/2" Ex-View IT CCD, 410K(PAL : 470K) pixles
Effective Pixels		NTSC : 768(H)x494(V) / PAL : 752(H)x582(V))
Scanning Method		2:1 Interlace
Scanning	Horizontal	NTSC : 15.750Hz / PAL : 15.625Hz
Line Frequency	Vertical	NTSC : 60Hz / PAL : 50Hz
Synchronization Method		Internal / Line lock (V PHASE control)
Horizontal	Color	540 TV Lines
Resolution	B/W	570 TV Lines
Signal Output		VBS 1.0Vp-p(75 ohm, composite)
S/N Ratio	S/N Ratio	50dB
	Mount Type	C/CS Mount Compatible
Minimum Scene Illumination	Color	0.0001(Sens up 256X, 15IRE)Lux
	B/W	0.00001(Sens up 256X, 15IRE)Lux
Functions	Privacy Zone	Off/On(24EA)
	Day & Night	DAY/NIGHT/AUTO/EXT
	Motion Detection	Off/On(4EA)
	D-Zoom	Off ~ 2X
	High Speed Shutter	Off ~ 1/10K sec
	Sens Up	Off ~ 256X
	BLC	Off/On(Area setting)
	AGC	Off/Low/High
	ELC	Off/On(Max. 1/100K sec)
	Line lock	Off/On
	Camera ID	Off/On
	White Balance	ATW1/ATW2/AWC/MANUAL
	OSD	Yes
Alarm Output		Yes(1EA)
Operating Temperature		-10°C ~ 50°C
Operating Humidity		Within 90% RH
Power Requirement		AC24V / DC12V compatible
Power Consumption		3.5W
Weight		410g
Dimensions		68(W) x 55(H) x 128.7(D)mm

* SCC-A2013P is same as SCC-A2313 except for Power Requirement (AC 220V~240V)